



Product Specification and Technical Data

PRODUCT: BG RF-7
Oil Treatment

PART NO.: 107

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F)	D 287	30.3
Specific Gravity @ 15.6°C (60°F).	D 1298	0.8743
Density,		
U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D 1250	7.289
Flash Point, COC	D 92	204°C (399°F)
Viscosity, cSt @ 100°C (212°F)	D 445.	353.70
Viscosity, cSt @ 40°C (104°F).	D 445.	3766.32
Viscosity Index	D 2270255
Pour Point	D 97	-12°C (10°F)
Color	D 1500	2.5
Color	Visual.	Light Amber

PROBLEM: High engine operating temperatures and heavy loads often cause engine oil to become so thin that it fails to provide a sufficient lubricating film. Continued high temperature operation will deplete necessary oil additives. When this occurs, oil will often oxidize and lose its ability to provide adequate engine protection.

SOLUTION: BG RF-7 is a specially developed formula for engine oil which helps increase engine compression and power by increasing the viscosity of the oil.

BG RF-7 contains additives that keep engine oil from oxidizing thus protecting internal engine parts from corrosive damage. BG RF-7 helps seal rings to increase compression and reduce blow-by. It will help reduce oil consumption and exhaust smoke and will reduce lifter and valve noise.

BG RF-7 is compatible with any petroleum base oil, synthetic and non-synthetic.

USAGE: Add one 11 oz. (325 mL) can of BG RF-7 to crankcase when oil is changed or between oil changes to bring oil level to full mark. One can treats engines with 4- or 5-quart (4- or 5-Liter) crankcase. Do not overfill.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.