



Product Specification and Technical Data

PRODUCT: BG 111
Engine Oil Supplement

PART NO.: 111

| TEST DATA: Test | ASTM Test Method | Typical Test Results |
|---|------------------|----------------------|
| API Gravity @ 15.6°C (60°F) | D 287 | 23.1 |
| Specific Gravity @ 15.6°C (60°F). | D 1298 | 0.9153 |
| Density, U.S. lbs./gal. (kg/L) @ 15.6°C (60°F) | D 1250 | 7.631 |
| Flash Point, COC | D 92 | 210°C (410°F) |
| Viscosity, cSt @ 100°C (212°F) | D 445. | 10.61 |
| Viscosity, cSt @ 40°C (104°F). | D 445. | 82.5 |
| Viscosity Index | D 2270 | .113 |
| Pour Point | D 97 | -34°C (-30°F) |

PROBLEM: Today's stop-and-go driving conditions and high ambient temperatures cause rapid depletion of critical oil additives. This leads to severe oxidation of the motor oil. Oxidation starts as heavy, black sludge in the crankcase, oil screens, oil passages, rocker arms and other critical areas of the engine.

SOLUTION: BG 111 Engine Oil Supplement has been designed to fortify engine oil and extend its useful life. Its unique blend of additives maintains engine cleanliness and performance under the most difficult, high stress operating conditions. Can be used in gasoline or diesel engines.

- BENEFITS:**
- Prevents oil thickening
 - Prevents oil oxidation
 - Prevents sludge and varnish deposits during stop-and-go driving
 - Protection against rust and corrosion
 - Provides greater power and performance
 - Reduces emissions

USAGE: Add one 11 oz. (325 mL) can of BG 111 Engine Oil Supplement to 4-5 quarts (4-5 Liters) of engine oil at each oil change. Add to crankcase any time the oil level is low to fortify the engine oil. Do not overfill crankcase.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.