



Product Specification and Technical Data

PRODUCT: BG Supercharge®

PART NO.: 200

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	45.5
	Specific Gravity @ 15.6°C (60°F)	D 1298	0.7993
	Density,		
	U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D 1250	6.664
	Flash Point, PMCC	D 93	35°C (96°F)
	Pour Point	D 97	<-51°C (<-60°F)
	Solubility in Water	Visual	Insoluble
	Color	Visual	Brown
	Color	D 1500	1.0

PROBLEM: Residues from commercially available gasoline will accumulate in intake manifolds, combustion chambers, on valves and in ports of modern engines. These deposits will disrupt efficient engine operation. This can cause severe driveability problems such as rough idle, loss of power, reduced fuel mileage and increased exhaust emissions.

SOLUTION: BG Supercharge® is a gasoline supplement that will keep the entire fuel system clean and free of deposits. It contains special stabilizers which prevent fuel oxidation, gum and varnish formation, thus providing excellent fuel storage stability. Catalytic converter and oxygen sensor safe.

- BENEFITS:**
- With regular use, keeps the entire fuel system clean
 - Prevents deposit formation
 - Improves engine performance
 - Restores optimum fuel economy
 - Reduces exhaust emissions
 - Eliminates driveability problems caused by deposit build-up

USAGE: Add 1 gallon (4 Liters) BG Supercharge® to 400 gallons (1,520 Liters) of gasoline. 6 ounces (177 mL) treats up to 15 gallons (57 Liters) of fuel.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.