



# Product Specification and Technical Data

**PRODUCT: BG Supercharge® II**

**PART NO.: 202**

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	45.5
	Specific Gravity @ 15.6°C (60°F)	D 1298	0.7993
	Density, U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D 1250	6.664
	Flash Point, PMCC	D 93	35°C (96°F)
	Pour Point	D 97	<-51°C (<-60°F)
	Initial Boiling Point	D 86	158°C (318°F)
	Color	Visual	Brown

**PROBLEM:** Residues from commercially available gasoline will accumulate in intake manifolds, on valves and in ports of modern engines. These deposits will interrupt the critical fuel/air ratio that is vital to efficient operation of the engine. This can cause severe driveability problems such as rough idle, loss of power, reduced fuel mileage and increased exhaust emissions.

**SOLUTION:** BG Supercharge® II is a gasoline supplement that will keep the entire fuel system clean and free of deposits. It contains special stabilizers which prevent fuel oxidation, gum and varnish formation, thus providing excellent fuel storage stability.

- BENEFITS:**
- With regular use, keeps the entire fuel system clean
  - Prevents deposit formation
  - Improves engine performance
  - Restores fuel economy
  - Reduces exhaust emissions
  - Eliminates driveability problems caused by deposit build-up.

**USAGE:** Pour BG Supercharge® II into the fuel tank. One 6 ounce (177 mL) bottle treats up to 15 gallons (57 Liters) of gasoline.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.