



# Product Specification and Technical Data

**PRODUCT: BG 207**  
Deposit Control Fuel Treatment

**PART NO.: 207**

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F) . . . . .	D 287 . . . . .	47.6
Specific Gravity @ 15.6°C (60°F). . . . .	D 1298 . . . . .	0.7902
Density, U.S. lbs./gal. (kg/L) @ 15.6°C (60°F) . . . . .	D 1250 . . . . .	6.588
Flash Point, PMCC . . . . .	D 93 . . . . .	40°C (104°F)
Color . . . . .	D 1500 . . . . .	0.5

**PROBLEM:** Residues from commercially available gasoline will accumulate in intake manifolds, on valves and in ports of modern engines. These deposits will interrupt the critical fuel/air ratio that is vital to efficient operation of the engine. This can cause severe driveability problems such as rough idle, loss of power, reduced fuel mileage and increased exhaust emissions.

**SOLUTION:** BG 207 Deposit Control Fuel Treatment is a gasoline supplement that will keep the entire fuel system clean and free of deposits. It contains special stabilizers which prevent fuel oxidation, gum and varnish formation, thus providing excellent fuel storage stability. BG 207 Deposit Control Fuel Treatment carries the BMW IV D (Intake valve cleanliness) approval. Catalytic converter and oxygen sensor safe.

- BENEFITS:**
- With regular use, keeps the entire fuel system clean.
  - Prevents deposit formation.
  - Improves engine performance.
  - Restores fuel economy.
  - Reduces exhaust emissions.
  - Eliminates driveability problems caused by deposit build-up.
  - Helps maintain new car performance.

**USAGE:** Pour BG 207 Deposit Control Fuel Treatment into the fuel tank. One 6 ounce (177 mL) bottle treats up to 15 gallons (57 Liters) of gasoline.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.