



Product Specification and Technical Data

PRODUCT: BG D'Icer

PART NO.: 233

TEST DATA: Test	Typical Test Results
Appearance	Clear Liquid
Odor	Slight Ether
Density, U.S. lbs./gal. @ 15.6°C (60°F).	7.66
Flash Point	31°C (88°F)
Specific Gravity (water=1)0.919
Solubility in water	Infinitely
Boiling Point	117°C (243°F)

PROBLEM: Water condensation and entrained moisture in diesel fuel can wreak havoc on an engine and fuel system. During cold weather, water freezes into tiny crystals that can plug fuel filters and starve the engine for fuel. Fuel system corrosion also increases as water in the fuel system comes into contact with metallic surfaces within the fuel injectors, fuel sending units, and other critical fuel management components.

SOLUTION: BG D'Icer is formulated to effectively isolate free moisture from #1 and #2 diesel fuel, enabling it to be absorbed in the fuel for combustion. When used as directed, BG D'Icer will prevent filter plugging caused by icing, fuel system corrosion and loss of power due to restricted fuel flow. This diesel fuel additive complies with the Federal low-sulfur content requirements for use in diesel motor vehicles. Catalytic converter and oxygen sensor safe.

USAGE: Add one gallon (4 Liters) BG D'Icer to 10,000 gallons (37,854 Liters) diesel fuel.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.