



## Product Specification and Technical Data

**PRODUCT: BG Fuel System Drier**  
for Gasoline Engines

**PART NO.: 280**

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	48.5
	Specific Gravity @ 15.6°C (60°F)	D 1298	0.786
	Density, U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D 1250	6.553
	Flash Point, TCC	D 56	11°C (53°F)
	Color	Visual	Clear

**PROBLEM:** Modern automotive fuels are susceptible to contamination by water through condensation formed during storage. Untreated, this moisture can contribute to corrosion of the fuel system, erratic engine operation, and the growth of microorganisms, which can plug fuel filters.

**SOLUTION:** BG Fuel System Drier for gasoline engines contains a safe and effective chemistry that absorbs moisture and allows it to be harmlessly burned by the engine. BG Fuel System Drier also helps provide easier cold weather starting and guards against fuel line freezing and carburetor icing.

**USAGE:** Add 12 ounces (355 mL) of BG Fuel System Drier to a tankful of gasoline. For smaller gasoline engines: Add 1 ounce (30 mL) of BG Fuel System Drier per each gallon (4 Liters) of fuel.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.