



Product Specification and Technical Data

PRODUCT: BG Rubberized Undercoating

PART NO.: 451

TEST DATA: Test	Typical Test Results
Specific Gravity (H ₂ O = 1)	0.935
Flash Point, TCC	-40°C (-40°F)
Vapor Pressure (psig) @ 21°C (70°F)	55-65
Solubility in Water	Negligible
Vapor Density (air = 1)	>1
Appearance	Black Viscous Liquid
Net Weight, oz. (grams)	17.75 (503)
Volume, fl. oz.	21.92

DESCRIPTION: BG Rubberized Undercoating is a premium rubber coating which offers superior erosion protection to metal and sound deadens against road noise. Seals out moisture, dries quickly, and provides a flexible finish that can be painted. If painted, a flexibilized enamel or lacquer will provide the best level of performance. However, because of the variety of paints available, no liability for checking, cracking or imperfections in the paint surface can be offered.

USAGE: For best results shake for a full minute after agitator ball moves freely. Repeat occasionally during use. Apply even coats from a distance of 12–18 inches. After using, invert can and spray to clear valve and actuator.
IMPORTANT: Avoid application closer than 10-12 inches (25-30 cm) from the exhaust system and catalytic converter.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.