



# Product Specification and Technical Data

**PRODUCT: BG Chain Lubricant for Farm & Industry**

**PART NO.: 495F**

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	27.9
	Specific Gravity @ 15.6°C (60°F)	D 1298	0.8876
	Density, U.S. lbs./gal. @ 15.6°C (60°F)	D 1250	7.4
	Flash Point, COC	D 92	260°C (500°F)
	Viscosity, cSt @ 100°C (212°F)	D 445	14.37
	Viscosity, cSt @ 40°C (104°F)	D 445	132.85
	Viscosity Index	D 2270	107
	Pour Point	D 97	-12°C (10°F)
	Color	Visual	Grey/Black
	Net Weight, oz. (grams)		15 (425)
	Volume, fl. oz.		13.44

**DESCRIPTION:** BG Chain Lubricant for Farm & Industry was developed specifically for roller chain lubrication. It foams on—no messy overspray—and is highly adhesive to metal surfaces. Contains Moly for added lubrication. Resistant to water washout. BG Chain Lubricant for Farm & Industry will not cause deterioration of chain components. Recommended for chains, slides and all applications where an adhesive oil lubricant is required.

For best results, chain should be clean and dry before applying BG Chain Lubricant for Farm & Industry. Apply lubricant to the inside of the chain, making sure to lubricate each chain roller.

This product is available in aerosol and liquid form.

**USAGE:** Shake well before using. Use extension to apply lubricant to exact area to be lubricated. Apply sparingly. For best results, clean chain before applying BG Chain Lubricant for Farm & Industry.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.