



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

## \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Part Number:** 206 (All Sizes)

**Product Use:** Air Intake System Cleaner

### Manufacturer Information

BG Products Inc.  
701 S. Wichita Street  
Wichita, KS 67213

Phone: (316) 265-2686  
Fax: (316) 265-0718  
Emergency # 1-800-424-9300 (CHEMTREC)

## \*\*\* Section 2 - Hazards Identification \*\*\*

### Emergency Overview

#### DANGER

- EXTREMELY FLAMMABLE! Do not use or store near flames, sparks, or hot surfaces.
- HARMFUL OR FATAL IF SWALLOWED!
- VAPOR HARMFUL! Avoid prolonged breathing of fumes. Use with adequate ventilation.
- EYE AND SKIN IRRITANT! This product is irritating to the eyes, respiratory system and skin.

**HMIS Ratings: Health: 3 Fire: 4 Physical Hazard: 0 Pers. Prot.: B**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

CAS #	Component	Percent
Not Available	PETROLEUM DISTILLATES	40-70
872-50-4	METHYL-1 PYRROLIDINONE-2	10-30
1330-20-7	XYLENE	10-20
67-63-0	ISOPROPYL ALCOHOL	7-13
67-64-1	ACETONE	7-13

### Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following:  
Petroleum distillates, hydrotreated light (64742-47-8).

### Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

## \*\*\* Section 4 - First Aid Measures \*\*\*

### First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

### First Aid: Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention.

### First Aid: Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

## First Aid: Inhalation

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.

## \*\*\* Section 5 - Fire Fighting Measures \*\*\*

### General Fire Hazards

See Section 9 for Flammability Properties.  
Keep away from heat, sparks, or open flame.

### Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

### Extinguishing Media

Dry chemical, foam, carbon dioxide.

### Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

### NFPA Ratings: Health: 3 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

### Containment Procedures

Contain the discharged material. Remove sources of ignition.

### Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material. Shovel material into appropriate container for disposal.

### Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

### Special Procedures

Wear appropriate personal protective equipment.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

### Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### A: Component Exposure Limits

#### XYLENE (1330-20-7)

ACGIH: 100 ppm TWA  
150 ppm STEL



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

OSHA: 100 ppm TWA; 435 mg/m<sup>3</sup> TWA  
150 ppm STEL; 655 mg/m<sup>3</sup> STEL

## ACETONE (67-64-1)

ACGIH: 500 ppm TWA  
750 ppm STEL  
OSHA: 750 ppm TWA; 1800 mg/m<sup>3</sup> TWA  
1000 ppm STEL; 2400 mg/m<sup>3</sup> STEL (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)  
NIOSH: 250 ppm TWA; 590 mg/m<sup>3</sup> TWA

## ISOPROPYL ALCOHOL (67-63-0)

ACGIH: 200 ppm TWA  
400 ppm STEL  
OSHA: 400 ppm TWA; 980 mg/m<sup>3</sup> TWA  
500 ppm STEL; 1225 mg/m<sup>3</sup> STEL  
NIOSH: 400 ppm TWA; 980 mg/m<sup>3</sup> TWA  
500 ppm STEL; 1225 mg/m<sup>3</sup> STEL

## B: Canadian Provincial Exposure Limits

### PETROLEUM DISTILLATES (Not Available)

British Columbia: 200 mg/m<sup>3</sup> TWA (as total hydrocarbon vapour) (related to Jet fuels)  
Columbia: Skin notation (related to Jet fuels)

### METHYL-1 PYRROLIDINONE-2 (872-50-4)

Ontario: 400 mg/m<sup>3</sup> TWAEV  
Yukon: 100 ppm TWA; 400 mg/m<sup>3</sup> TWA  
125 ppm STEL; 500 mg/m<sup>3</sup> STEL

### XYLENE (1330-20-7)

Alberta: 100 ppm TWA; 434 mg/m<sup>3</sup> TWA  
150 ppm STEL; 651 mg/m<sup>3</sup> STEL  
British Columbia: 100 ppm TWA  
Columbia: 150 ppm STEL  
Manitoba: 100 ppm TWA  
150 ppm STEL  
New Brunswick: 100 ppm TWA; 434 mg/m<sup>3</sup> TWA  
150 ppm STEL; 651 mg/m<sup>3</sup> STEL  
NW Territories: 100 ppm TWA; 434 mg/m<sup>3</sup> TWA  
150 ppm STEL; 652 mg/m<sup>3</sup> STEL  
Skin notation  
Nova Scotia: 100 ppm TWA  
150 ppm STEL  
Nunavut: 100 ppm TWA; 434 mg/m<sup>3</sup> TWA  
150 ppm STEL; 652 mg/m<sup>3</sup> STEL  
Skin notation  
Ontario: 100 ppm TWAEV; 435 mg/m<sup>3</sup> TWAEV  
150 ppm STEV; 650 mg/m<sup>3</sup> STEV  
Quebec: 150 ppm STEV; 651 mg/m<sup>3</sup> STEV  
100 ppm TWAEV; 434 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 434 mg/m<sup>3</sup> TWA; 100 ppm TWA  
651 mg/m<sup>3</sup> STEL; 150 ppm STEL  
Yukon: 100 ppm TWA; 435 mg/m<sup>3</sup> TWA  
150 ppm STEL; 650 mg/m<sup>3</sup> STEL  
Skin notation

### ACETONE (67-64-1)

Alberta: 750 ppm TWA; 1800 mg/m<sup>3</sup> TWA  
1000 ppm STEL; 2400 mg/m<sup>3</sup> STEL  
British Columbia: 250 ppm TWA



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

Columbia:	500 ppm STEL
Manitoba:	500 ppm TWA 750 ppm STEL
New	500 ppm TWA; 1188 mg/m3 TWA
Brunswick:	750 ppm STEL; 1782 mg/m3 STEL
NW Territories:	1000 ppm TWA; 2370 mg/m3 TWA 1250 ppm STEL; 2970 mg/m3 STEL
Nova Scotia:	500 ppm TWA 750 ppm STEL
Nunavut:	1000 ppm TWA; 2370 mg/m3 TWA 1250 ppm STEL; 2970 mg/m3 STEL
Ontario:	500 ppm TWAEV 750 ppm STEV
Quebec:	1000 ppm STEV; 2380 mg/m3 STEV 500 ppm TWAEV; 1190 mg/m3 TWAEV
Saskatchewan:	1780 mg/m3 TWA; 750 ppm TWA 2380 mg/m3 STEL; 1000 ppm STEL
Yukon:	1000 ppm TWA; 2400 mg/m3 TWA 1250 ppm STEL; 3000 mg/m3 STEL

## ISOPROPYL ALCOHOL (67-63-0)

Alberta:	400 ppm TWA; 983 mg/m3 TWA 500 ppm STEL; 1230 mg/m3 STEL
British	200 ppm TWA
Columbia:	400 ppm STEL
Manitoba:	200 ppm TWA 400 ppm STEL
New	400 ppm TWA; 983 mg/m3 TWA
Brunswick:	500 ppm STEL; 1230 mg/m3 STEL
NW Territories:	400 ppm TWA; 983 mg/m3 TWA 500 ppm STEL; 1228 mg/m3 STEL Skin notation
Nova Scotia:	200 ppm TWA 400 ppm STEL
Nunavut:	400 ppm TWA; 983 mg/m3 TWA 500 ppm STEL; 1228 mg/m3 STEL Skin notation
Ontario:	200 ppm TWAEV 400 ppm STEV
Quebec:	500 ppm STEV; 1230 mg/m3 STEV 400 ppm TWAEV; 983 mg/m3 TWAEV
Saskatchewan:	983 mg/m3 TWA; 400 ppm TWA 1230 mg/m3 STEL; 500 ppm STEL
Yukon:	400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL Skin notation

## Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

## PERSONAL PROTECTIVE EQUIPMENT

### Personal Protective Equipment: Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

### Personal Protective Equipment: Skin

Use appropriate hand protection.

### Personal Protective Equipment: Respiratory



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

## Personal Protective Equipment: General

Use good industrial hygiene practices in handling this material.

### \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance:</b>	Light Yellow	<b>Odor:</b>	Solvent
<b>Physical State:</b>	Liquid	<b>Flash Point:</b>	-14°C (0°F)
<b>Flash Point Method:</b>	TCC	<b>Boiling Point:</b>	Not Available
<b>Melting Point:</b>	Not Available	<b>Pour Point:</b>	-54°C (-65°F)
<b>Specific Gravity:</b>	0.8534	<b>Bulk Density:</b>	7.115 lbs/gal
<b>Solubility (H2O):</b>	Insoluble	<b>Vapor Pressure:</b>	Not Available
<b>Vapor Density:</b>	Not Available	<b>Auto Ignition:</b>	Not Available
<b>Lower Flammability Limit:</b>	Not Available	<b>Upper Flammability Limit:</b>	Not Available
<b>pH:</b>	Not Available		

### \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

#### Chemical Stability

Stable under normal conditions.

#### Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

#### Incompatibility

This product may react with oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

#### Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

#### Possibility of Hazardous Reactions

Will not occur.

### \*\*\* Section 11 - Toxicological Information \*\*\*

#### Acute Dose Effects

##### A: General Product Information

An LD50 value for this product has not been determined.

##### B: Component Analysis - LD50/LC50

###### PETROLEUM DISTILLATES (Not Available)

Inhalation LC50 Rat: >5.2 mg/L/4H; Oral LD50 Rat: >5000 mg/kg; Dermal LD50 Rabbit: >2000 mg/kg (related to Petroleum distillates, hydrotreated light)

###### METHYL-1 PYRROLIDINONE-2 (872-50-4)

Inhalation LC50 Rat: 3.1 mg/L/4H; Oral LD50 Rat: 3598 mg/kg; Dermal LD50 Rat: 2500 mg/kg; Dermal LD50 Rabbit: 2000 mg/kg

###### XYLENE (1330-20-7)

Inhalation LC50 Rat: 5000 ppm/4H; Oral LD50 Rat: 4300 mg/kg; Dermal LD50 Rabbit: >1700 mg/kg

###### ACETONE (67-64-1)

Inhalation LC50 Rat: 76 mg/L/4H; Oral LD50 Rat: 1800 mg/kg; Dermal LD50 Rabbit: 20000 mg/kg



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

## ISOPROPYL ALCOHOL (67-63-0)

Inhalation LC50 Rat: 72.6 mg/L/4H; Oral LD50 Rat:4396 mg/kg; Dermal LD50 Rat:12800 mg/kg; Dermal LD50 Rabbit:12870 mg/kg

## Carcinogenicity

### A: General Product Information

No carcinogenicity data available for this product.

### B: Component Carcinogenicity

#### XYLENE (1330-20-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71 [1999], Monograph 47 [1989] (Group 3 (not classifiable))

#### ACETONE (67-64-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

#### ISOPROPYL ALCOHOL (67-63-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71 [1999], Supplement 7 [1987], Monograph 15 [1977] (Group 3 (not classifiable))

## \*\*\* Section 12 - Ecological Information \*\*\*

## Ecotoxicity

No information available for the product.

## \*\*\* Section 13 - Disposal Considerations \*\*\*

## Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

## \*\*\* Section 14 - Transportation Information \*\*\*

## US DOT Information

206:

Shipping Name: Consumer Commodity, ORM-D

2065, 20653:

Shipping Name: Flammable Liquid, n.o.s. (contains Methyl-1-Pyrrolidinone-2 and Xylene)

UN/NA #: 1993 Hazard Class: 3 Packing Group: II

Required Label(s): Flammable Liquid

## IMDG Information

206:

Shipping Name: Flammable Liquid, n.o.s. (contains Methyl-1-Pyrrolidinone-2 and Xylene)

UN #: 1993 Hazard Class: 3 Packing Group: II Flash Point: -14°C

Required Label(s): Limited Quantity

2065, 20653:

Shipping Name: Flammable Liquid, n.o.s. (contains Methyl-1-Pyrrolidinone-2 and Xylene)

UN #: 1993 Hazard Class: 3 Packing Group: II Flash Point: -14°C

Required Label(s): Flammable



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

## IATA Information

**206:**

**Shipping Name:** Flammable Liquid, n.o.s. (contains Methyl-1-Pyrrolidinone-2 and Xylene)

**UN #:** 1993 **Hazard Class:** 3 **Packing Group:** II **Flash Point:** -14°C

**Required Label(s):** Limited Quantity

**2065:**

**Shipping Name:** Flammable Liquid, n.o.s. (contains Methyl-1-Pyrrolidinone-2 and Xylene)

**UN #:** 1993 **Hazard Class:** 3 **Packing Group:** II **Flash Point:** -14°C

**Required Label(s):** Flammable

**20653: CAN NOT SHIP BY AIR**

## \*\*\* Section 15 - Regulatory Information \*\*\*

### US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.

#### A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

##### **METHYL-1 PYRROLIDINONE-2 (872-50-4)**

SARA 313: 1.0 % de minimis concentration

##### **XYLENE (1330-20-7)**

SARA 313: 1.0 % de minimis concentration

CERCLA: 100 lb final RQ; 45.4 kg final RQ

##### **ACETONE (67-64-1)**

CERCLA: 5000 lb final RQ; 2270 kg final RQ

##### **ISOPROPYL ALCOHOL (67-63-0)**

SARA 313: 1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)

#### B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
METHYL-1 PYRROLIDINONE-2	872-50-4	Yes	DSL	EINECS
XYLENE	1330-20-7	Yes	DSL	EINECS
ACETONE	67-64-1	Yes	DSL	EINECS
ISOPROPYL ALCOHOL	67-63-0	Yes	DSL	EINECS

### State Regulations

Other state regulations may apply. Check individual state requirements.

#### Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
METHYL-1 PYRROLIDINONE-2	872-50-4	No	Yes	Yes	No	Yes	No
XYLENE	1330-20-7	Yes	Yes	Yes	Yes	Yes	Yes
ACETONE	67-64-1	Yes	Yes	Yes	Yes	Yes	Yes
ISOPROPYL ALCOHOL	67-63-0	Yes	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement



# Material Safety Data Sheet

Air Intake System Cleaner

MSDS ID: 206

Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

## Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
ACETONE	67-64-1	1 %
ISOPROPYL ALCOHOL	67-63-0	1 %

## \*\*\* Section 16 - Other Information \*\*\*

### Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

### Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

Contact: Kolin Anglin, Environmental Coordinator

Contact Phone: 316-265-2686

End of MSDS 206