



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

*** Section 1 - Chemical Product and Company Identification ***

Part Number: 2152, 2155, 21530, 21553

Product Use: Diesel Fuel Pour Depressant

Manufacturer Information

BG Products Inc.
701 S. Wichita Street
Wichita, KS 67213

Phone: (316) 265-2686
Fax: (316) 265-0718
Emergency # 1-800-424-9300 (CHEMTREC)

*** Section 2 - Hazards Identification ***

Emergency Overview

CAUTION

- COMBUSTIBLE! Do not use or store near flames, sparks, or hot surfaces.
- EYE AND SKIN IRRITANT! This product is irritating to the eyes, respiratory system and skin.
- This product may be harmful if it is swallowed.
- This product may be harmful by inhalation.

HMIS Ratings: Health: 2 Fire: 2 Physical Hazard: 0 Pers. Prot.: B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
Not Available	PETROLEUM DISTILLATES	60-100
Not Available	ETHYLENE VINYL ACETATE COPOLYMER	30-60
91-20-3	NAPHTHALENE	5-10
1330-20-7	XYLENE	0.5-1.5

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following:
Naphtha (petroleum), heavy aromatic (64742-94-5), PETROLEUM BASE OIL (8008-20-6).

Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

*** Section 4 - First Aid Measures ***

Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention.

Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

Inhalation

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.
Keep this product from heat, sparks, or open flame.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing.
Fire fighters should avoid inhaling any combustion products.

NFPA Ratings: Health: 2 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Contain the discharged material. Remove sources of ignition.

Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material.
Shovel material into appropriate container for disposal.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

Special Procedures

Wear appropriate personal protective equipment.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

PETROLEUM DISTILLATES (Not Available)

ACGIH: 200 mg/m3 TWA (application restricted to conditions in which there are negligible aerosol)



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

exposures) (related to Kerosene)

Skin - potential significant contribution to overall exposure by the cutaneous route
(related to Kerosene)

NIOSH: 100 mg/m³ TWA (related to Kerosene)

NAPHTHALENE (91-20-3)

ACGIH: 10 ppm TWA

15 ppm STEL

Skin - potential significant contribution to overall exposure by the cutaneous route

OSHA: 10 ppm TWA; 50 mg/m³ TWA

15 ppm STEL; 75 mg/m³ STEL

NIOSH: 10 ppm TWA; 50 mg/m³ TWA

15 ppm STEL; 75 mg/m³ STEL

XYLENE (1330-20-7)

ACGIH: 100 ppm TWA

150 ppm STEL

OSHA: 100 ppm TWA; 435 mg/m³ TWA

150 ppm STEL; 655 mg/m³ STEL

B: Canadian Provincial Exposure Limits

PETROLEUM DISTILLATES (Not Available)

British Columbia: 200 mg/m³ TWA (as total hydrocarbon vapour) (related to Kerosene)

Manitoba: Skin notation (related to Kerosene)

200 mg/m³ TWA (application restricted to conditions in which there are negligible aerosol exposures) (related to Kerosene)

Skin - potential significant contribution to overall exposure by the cutaneous route
(related to Kerosene)

Nova Scotia: 200 mg/m³ TWA (application restricted to conditions in which there are negligible aerosol exposures) (related to Kerosene)

Skin - potential significant contribution to overall exposure by the cutaneous route
(related to Kerosene)

Ontario: 200 mg/m³ TWAEV (as total hydrocarbon vapour) (related to Kerosene)

Absorption through skin, eyes, or mucous membranes (related to Kerosene)

NAPHTHALENE (91-20-3)

Alberta: 10 ppm TWA; 52 mg/m³ TWA

15 ppm STEL; 79 mg/m³ STEL

Substance may be readily absorbed through intact skin

British Columbia: 10 ppm TWA

Manitoba: 15 ppm STEL

Skin notation

Ontario: 10 ppm TWA

15 ppm STEL

Skin - potential significant contribution to overall exposure by the cutaneous route

New Brunswick: 10 ppm TWA; 52 mg/m³ TWA

NW Territories: 15 ppm STEL; 79 mg/m³ STEL

10 ppm TWA; 52 mg/m³ TWA

15 ppm STEL; 79 mg/m³ STEL

Nova Scotia: 10 ppm TWA

15 ppm STEL

Skin - potential significant contribution to overall exposure by the cutaneous route

Nunavut: 10 ppm TWA; 52 mg/m³ TWA

15 ppm STEL; 79 mg/m³ STEL

Ontario: 10 ppm TWAEV; 52 mg/m³ TWAEV

15 ppm STEV; 78 mg/m³ STEV

Quebec: 15 ppm STEV; 79 mg/m³ STEV

10 ppm TWAEV; 52 mg/m³ TWAEV

Saskatchewan: 52 mg/m³ TWA; 10 ppm TWA



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

Yukon: 79 mg/m3 STEL; 15 ppm STEL
10 ppm TWA; 50 mg/m3 TWA
15 ppm STEL; 75 mg/m3 STEL

XYLENE (1330-20-7)

Alberta: 100 ppm TWA; 434 mg/m3 TWA
150 ppm STEL; 651 mg/m3 STEL
British Columbia: 100 ppm TWA
Manitoba: 100 ppm TWA
150 ppm STEL
New Brunswick: 100 ppm TWA; 434 mg/m3 TWA
150 ppm STEL; 651 mg/m3 STEL
NW Territories: 100 ppm TWA; 434 mg/m3 TWA
150 ppm STEL; 652 mg/m3 STEL
Skin notation
Nova Scotia: 100 ppm TWA
150 ppm STEL
Nunavut: 100 ppm TWA; 434 mg/m3 TWA
150 ppm STEL; 652 mg/m3 STEL
Skin notation
Ontario: 100 ppm TWAEV; 435 mg/m3 TWAEV
150 ppm STEV; 650 mg/m3 STEV
Quebec: 150 ppm STEV; 651 mg/m3 STEV
100 ppm TWAEV; 434 mg/m3 TWAEV
Saskatchewan: 434 mg/m3 TWA; 100 ppm TWA
651 mg/m3 STEL; 150 ppm STEL
Yukon: 100 ppm TWA; 435 mg/m3 TWA
150 ppm STEL; 650 mg/m3 STEL
Skin notation

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

General

Use good industrial hygiene practices in handling this material.

Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

Skin

Use appropriate hand protection.

Respiratory

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

***** Section 9 - Physical & Chemical Properties *****

Appearance: Amber	Odor: Solvent
Physical State: Liquid	Flash Point: 61°C (141°F)
Flash Point Method: PMCC	Boiling Point: Not Available
Melting Point: Not Determined	Pour Point: -43°C (-45°F)
Specific Gravity: 0.9165	Bulk Density: 7.641 lbs/gal
Solubility (H2O): Insoluble	Vapor Pressure: Not Determined
Vapor Density: Not Determined	Auto Ignition: Not available
Lower Flammability Limit: Not available	Upper Flammability Limit: Not available



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

pH: Not available

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

Incompatibility

This product may react with strong oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Decomposition of this product may emit oxides of nitrogen.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

An LD50 value for this product has not been determined.

B: Component Analysis - LD50/LC50

PETROLEUM DISTILLATES (Not Available)

Inhalation LC50 Rat: 590 mg/m³/4H; Oral LD50 Rat: 7050 mg/kg; Dermal LD50 Rabbit: 2 mL/kg (related to Naphtha (petroleum), heavy aromatic)

NAPHTHALENE (91-20-3)

Inhalation LC50 Rat: >340 mg/m³/1H; Oral LD50 Rat: 490 mg/kg; Dermal LD50 Rat: 2500 mg/kg; Dermal LD50 Rabbit: >20 g/kg

XYLENE (1330-20-7)

Inhalation LC50 Rat: 5000 ppm/4H; Oral LD50 Rat: 4300 mg/kg; Dermal LD50 Rabbit: >1700 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

PETROLEUM DISTILLATES (Not Available)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans (related to Kerosene)

NAPHTHALENE (91-20-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

NTP: Reasonably Anticipated To Be A Carcinogen (Possible Select Carcinogen)

IARC: Monograph 82 [2002] (Group 2B (possibly carcinogenic to humans))

XYLENE (1330-20-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

IARC: Monograph 71 [1999], Monograph 47 [1989] (Group 3 (not classifiable))

***** Section 12 - Ecological Information *****

Ecotoxicity

No information available for the product.

***** Section 13 - Disposal Considerations *****

Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

***** Section 14 - Transportation Information *****

US DOT Information

Shipping Name: Lubricating Oil, Not Regulated

IMDG Information

Shipping Name: Lubricating Oil, Not Regulated

IATA Information

Shipping Name: Lubricating Oil, Not Regulated

***** Section 15 - Regulatory Information *****

US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.

A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

NAPHTHALENE (91-20-3)

SARA 313: 0.1 % de minimis concentration
CERCLA: 100 lb final RQ; 45.4 kg final RQ

XYLENE (1330-20-7)

CERCLA: 100 lb final RQ; 45.4 kg final RQ

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
NAPHTHALENE	91-20-3	Yes	DSL	EINECS
XYLENE	1330-20-7	Yes	DSL	EINECS

State Regulations

Other state regulations may apply. Check individual state requirements.

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Petroleum Distillates (1related to Kerosine) (2related to Kerosene)	Not Available	No	Yes 1	No	Yes 2	Yes 1	Yes 2
NAPHTHALENE	91-20-3	Yes	Yes	Yes	Yes	Yes	Yes



Material Safety Data Sheet

Diesel Fuel Pour Depressant

MSDS ID: 215

XYLENE	1330-20-7	Yes	Yes	Yes	Yes	Yes	Yes
--------	-----------	-----	-----	-----	-----	-----	-----

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
NAPHTHALENE	91-20-3	1 %

* * * Section 16 - Other Information * * *

Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

Contact: Kolin Anglin, Environmental Coordinator

Contact Phone: 316-265-2686

End of MSDS 215