



Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

*** Section 1 - Chemical Product and Company Identification ***

Part Number: 2401, 2405, 24016, 24030, 24053, 240B

Product Use: Biodiesel Fuel Treatment

Manufacturer Information

BG Products Inc.
701 S. Wichita Street
Wichita, KS 67213 USA
www.bgprod.com

Phone: (800) 961-6228 or (316) 265-2686
Fax: (316) 265-1082
Emergency # 1-800-424-9300 (CHEMTREC)

*** Section 2 - Hazards Identification ***

Emergency Overview

CAUTION

- COMBUSTIBLE! Do not use or store near flames, sparks, or hot surfaces.
- EYE, SKIN, AND RESPIRATORY IRRITANT. This product is irritating to the eyes, skin, and respiratory system. Avoid contact with eyes, skin, and clothing. Avoid prolonged breathing of fumes.
- This product may be harmful by inhalation. Use with adequate ventilation.
- This product may be harmful if it is swallowed.

HMIS Ratings: Health: 1 Fire: 2 Physical Hazard: 0 Pers. Prot.: B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
64742-94-5	AROMATIC HYDROCARBON	40-70
Not Available	ETHYLENE VINYL ACETATE COPOLYMER	10-30
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	7-13
91-20-3	NAPHTHALENE	3-7
178535-25-6	Light Ends of Polyethylbenzene Residue	3-7
Not Available	Detergent	1-5
Not Available	Butylated Phenol	1-5
95-63-6	1,2,4-TRIMETHYLBENZENE	0.5-1.5

Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

*** Section 4 - First Aid Measures ***

Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention.

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.

Inhalation

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.
Keep away from heat, sparks, or open flame.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

NFPA Ratings: Health: 1 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Contain the discharged material. Remove sources of ignition.

Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material. Shovel material into appropriate container for disposal.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

Special Procedures

Wear appropriate personal protective equipment.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2)

ACGIH: 100 ppm TWA
150 ppm STEL
OSHA: 100 ppm TWA; 360 mg/m3 TWA
150 ppm STEL; 540 mg/m3 STEL
NIOSH: 100 ppm TWA; 360 mg/m3 TWA
150 ppm STEL; 540 mg/m3 STEL

NAPHTHALENE (91-20-3)

ACGIH: 10 ppm TWA
15 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route
OSHA: 10 ppm TWA; 50 mg/m3 TWA
15 ppm STEL; 75 mg/m3 STEL
NIOSH: 10 ppm TWA; 50 mg/m3 TWA
15 ppm STEL; 75 mg/m3 STEL

1,2,4-TRIMETHYLBENZENE (95-63-6)

NIOSH: 25 ppm TWA; 125 mg/m3 TWA

B: Canadian Provincial Exposure Limits

PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2)

Alberta: 100 ppm TWA; 369 mg/m3 TWA
150 ppm STEL; 553 mg/m3 STEL
British Columbia: 50 ppm TWA
75 ppm STEL
Manitoba: 100 ppm TWA
150 ppm STEL
New Brunswick: 100 ppm TWA; 369 mg/m3 TWA
150 ppm STEL; 553 mg/m3 STEL
NW Territories: 100 ppm TWA; 360 mg/m3 TWA
150 ppm STEL; 540 mg/m3 STEL
Nova Scotia: 100 ppm TWA
150 ppm STEL
Nunavut: 100 ppm TWA; 360 mg/m3 TWA
150 ppm STEL; 540 mg/m3 STEL
Ontario: 100 ppm TWAEV; 365 mg/m3 TWAEV
150 ppm STEV; 550 mg/m3 STEV
Quebec: 150 ppm STEV; 553 mg/m3 STEV
100 ppm TWAEV; 369 mg/m3 TWAEV
Saskatchewan: 100 ppm TWA
150 ppm STEL
Yukon: 100 ppm TWA; 360 mg/m3 TWA
150 ppm STEL; 450 mg/m3 STEL

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

NAPHTHALENE (91-20-3)

Alberta:	10 ppm TWA; 52 mg/m3 TWA 15 ppm STEL; 79 mg/m3 STEL Substance may be readily absorbed through intact skin
British Columbia:	10 ppm TWA 15 ppm STEL Skin notation
Manitoba:	10 ppm TWA 15 ppm STEL Skin - potential significant contribution to overall exposure by the cutaneous route
New Brunswick:	10 ppm TWA; 52 mg/m3 TWA 15 ppm STEL; 79 mg/m3 STEL
NW Territories:	10 ppm TWA; 52 mg/m3 TWA 15 ppm STEL; 79 mg/m3 STEL
Nova Scotia:	10 ppm TWA 15 ppm STEL Skin - potential significant contribution to overall exposure by the cutaneous route
Nunavut:	10 ppm TWA; 52 mg/m3 TWA 15 ppm STEL; 79 mg/m3 STEL
Ontario:	10 ppm TWAEV; 52 mg/m3 TWAEV 15 ppm STEV; 78 mg/m3 STEV
Quebec:	15 ppm STEV; 79 mg/m3 STEV 10 ppm TWAEV; 52 mg/m3 TWAEV
Saskatchewan:	10 ppm TWA 15 ppm STEL
Yukon:	10 ppm TWA; 50 mg/m3 TWA 15 ppm STEL; 75 mg/m3 STEL

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

General

Use good industrial hygiene practices in handling this material. Avoid inhalation of mists/vapors and contact with skin and eyes.

Skin

Use appropriate hand protection.

Respiratory

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

Eyes

Wear safety glasses; chemical goggles (if splashing is possible).

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Amber	Odor:	Petroleum
Physical State:	Liquid	Flash Point:	42°C (107°F)
Flash Point Method:	PMCC	Boiling Point:	Not Determined
Melting Point:	Not Determined	Pour Point:	-15°C (4°F)
Specific Gravity:	0.9148	Bulk Density:	7.627 lbs/gal
Solubility (H2O):	Insoluble	Viscosity @ 40°C:	10.26
Vapor Pressure:	Not Determined	Vapor Density:	Not Determined
Auto Ignition:	Not Determined	Lower Flammability Limit:	Not Determined
Upper Flammability Limit:	Not Determined	pH:	Not Determined

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

Incompatibility

This product may react with oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

An LD50 value for this product has not been determined.

B: Component Analysis - LD50/LC50

AROMATIC HYDROCARBON (64742-94-5)

Inhalation LC50 Rat: 590 mg/m³/4H; Oral LD50 Rat: 7050 mg/kg; Dermal LD50 Rabbit: 2 mL/kg

PROPYLENE GLYCOL MONOMETHYL ETHER (107-98-2)

Inhalation LC50 Rat: 54.6 mg/L/4H; Inhalation LC50 Rat:>24 mg/L/1H; Oral LD50 Rat:5200 mg/kg; Dermal LD50 Rabbit:13000 mg/kg

NAPHTHALENE (91-20-3)

Inhalation LC50 Rat: >340 mg/m³/1H; Oral LD50 Rat:490 mg/kg; Dermal LD50 Rat:>2500 mg/kg; Dermal LD50 Rabbit:>20 g/kg

1,2,4-TRIMETHYLBENZENE (95-63-6)

Inhalation LC50 Rat: 18 g/m³/4H; Oral LD50 Rat:3400 mg/kg; Dermal LD50 Rabbit:>3160 mg/kg

Carcinogenicity

A: General Product Information

No carcinogenicity data available for this product.

B: Component Carcinogenicity

NAPHTHALENE (91-20-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

NTP: Reasonably Anticipated To Be A Human Carcinogen (Possible Select Carcinogen)

IARC: Monograph 82 [2002] (Group 2B (possibly carcinogenic to humans))

*** Section 12 - Ecological Information ***

Ecotoxicity

No information available for the product.

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

*** Section 13 - Disposal Considerations ***

Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

*** Section 14 - Transportation Information ***

US DOT Information

Shipping Name: 2401: Consumer Commodity, ORM-D

Shipping Name: 2405, 24016, 24030, 24053, 240B:

UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII

Required Label(s): Flammable

IMDG Information

Shipping Name: 2401: UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII, (42°C), Limited Quantity

Required Label(s): Limited Quantity

Shipping Name: 2405, 24016, 24030, 24053, 240B:

UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII, (42°C)

Required Label(s): Flammable

IATA Information

Shipping Name: 2401: UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII, (42°C), Limited Quantity

Required Label(s): Limited Quantity

Shipping Name: 2405: UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII, (42°C)

Required Label(s): Flammable

Shipping Name: 24016, 24030, 24053:

UN1993, Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon and Naphthalene), 3, PGIII, (42°C), CARGO AIRCRAFT ONLY

Required Label(s): Flammable, CARGO AIRCRAFT ONLY

Shipping Name: 240B: CAN NOT SHIP BY AIR

*** Section 15 - Regulatory Information ***

US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.

A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

NAPHTHALENE (91-20-3)

SARA 313: 0.1 % de minimis concentration

CERCLA: 100 lb final RQ; 45.4 kg final RQ

1,2,4-TRIMETHYLBENZENE (95-63-6)

SARA 313: 1.0 % de minimis concentration

Material Safety Data Sheet

Biodiesel Fuel Conditioner

MSDS ID: 240

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
AROMATIC HYDROCARBON	64742-94-5	Yes	DSL	EINECS
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	Yes	DSL	EINECS
NAPHTHALENE	91-20-3	Yes	DSL	EINECS
Light Ends of Polyethylbenzene Residue	178535-25-6	Yes	DSL	No
1,2,4-TRIMETHYLBENZENE	95-63-6	Yes	DSL	EINECS

State Regulations

Other state regulations may apply. Check individual state requirements.

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	Yes	Yes	Yes	Yes	Yes	Yes
NAPHTHALENE	91-20-3	Yes	Yes	Yes	Yes	Yes	Yes
1,2,4-TRIMETHYLBENZENE	95-63-6	No	Yes	Yes	Yes	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	1 %
NAPHTHALENE	91-20-3	1 %
1,2,4-TRIMETHYLBENZENE	95-63-6	0.1 %

*** Section 16 - Other Information ***

Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

Contact Information

Kolin Anglin, Environmental Coordinator
(316) 265-2686
msds@bgprod.com

End of MSDS 240