



# Material Safety Data Sheet

Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

## \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Part Number:** 451

**Product Use:** Undercoating and sound deadening applications for motor vehicles

### Manufacturer Information

BG Products Inc.  
701 S. Wichita Street  
Wichita, KS 67213

Phone: (316) 265-2686  
Fax: (316) 265-0718  
Emergency # 1-800-424-9300 (CHEMTREC)

## \*\*\* Section 2 - Hazards Identification \*\*\*

### Emergency Overview

#### DANGER

- CONTENTS UNDER PRESSURE.
- EXTREMELY FLAMMABLE. Vapors may cause flash fire or explosion.
- HARMFUL OR FATAL IF SWALLOWED. Severe and permanent damage to the mouth, throat and stomach may result from swallowing this product.
- EYE AND SKIN IRRITANT. Liquid or vapors may irritate the eyes. Symptoms include itching, burning, redness and tearing. Prolonged or repeated contact may result in defatting and drying of the skin, which may result in skin irritation or dermatitis (rash).
- This product may be harmful by inhalation. Avoid prolonged breathing of fumes. Use with adequate ventilation.

**HMIS Ratings: Health: 2 Fire: 4 Physical Hazard: 0 Pers. Prot.: B**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

CAS #	Component	Percent
68476-86-8	Petroleum gases, liquified, sweetened	15-40
79-20-9	Methyl acetate	7-13
8032-32-4	LIGHT ALIPHATIC SOLVENT NAPHTHA	7-13
108-88-3	Toluene	7-13
84-74-2	Dibutyl phthalate	3-7
67-56-1	METHANOL	1
64742-94-5	Naphtha (petroleum), heavy aromatic	1
142-82-5	Heptane (n-)	1
64742-16-1	Petroleum resins	1
1333-86-4	Carbon black	1

### Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

## \*\*\* Section 4 - First Aid Measures \*\*\*

### First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

### First Aid: Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation



# Material Safety Data Sheet

**Spray Rubberized Undercoating (Aerosol)**

**MSDS ID: 451**

persists, get medical attention.

## First Aid: Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.

## First Aid: Inhalation

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.

## \*\*\* Section 5 - Fire Fighting Measures \*\*\*

### General Fire Hazards

See Section 9 for Flammability Properties.  
Keep away from heat, sparks, or open flame.

### Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

### Extinguishing Media

Dry chemical, foam, carbon dioxide.

### Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

**NFPA Ratings: Health: 2 Fire: 4 Reactivity: 0 Other: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

### Containment Procedures

Contain the discharged material. Remove sources of ignition.

### Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material. Shovel material into appropriate container for disposal.

### Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

### Special Procedures

Wear appropriate personal protective equipment.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

### Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.



# Material Safety Data Sheet

Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

\*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

## A: Component Exposure Limits

### Toluene (108-88-3)

ACGIH: 20 ppm TWA  
OSHA: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL  
NIOSH: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL

### Methyl acetate (79-20-9)

ACGIH: 200 ppm TWA  
250 ppm STEL  
OSHA: 200 ppm TWA; 610 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL  
NIOSH: 200 ppm TWA; 610 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL

### Light Aliphatic Solvent Naphtha (8032-32-4)

ACGIH: 300 ppm TWA  
OSHA: 300 ppm TWA; 1350 mg/m<sup>3</sup> TWA  
400 ppm STEL; 1800 mg/m<sup>3</sup> STEL  
NIOSH: 350 mg/m<sup>3</sup> TWA  
1800 mg/m<sup>3</sup> Ceiling (15 min)

### Dibutyl phthalate (84-74-2)

ACGIH: 5 mg/m<sup>3</sup> TWA  
OSHA: 5 mg/m<sup>3</sup> TWA  
NIOSH: 5 mg/m<sup>3</sup> TWA

### Heptane (n-) (142-82-5)

ACGIH: 400 ppm TWA  
500 ppm STEL  
OSHA: 400 ppm TWA; 1600 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2000 mg/m<sup>3</sup> STEL  
NIOSH: 85 ppm TWA; 350 mg/m<sup>3</sup> TWA  
440 ppm Ceiling (15 min); 1800 mg/m<sup>3</sup> Ceiling (15 min)

### Carbon black (1333-86-4)

ACGIH: 3.5 mg/m<sup>3</sup> TWA  
OSHA: 3.5 mg/m<sup>3</sup> TWA  
NIOSH: 3.5 mg/m<sup>3</sup> TWA; 0.1 mg/m<sup>3</sup> TWA (as PAH, carbon black in presence of polycyclic aromatic hydrocarbons)

### Methanol (67-56-1)

ACGIH: 200 ppm TWA  
250 ppm STEL  
Skin - potential significant contribution to overall exposure by the cutaneous route  
OSHA: 200 ppm TWA; 260 mg/m<sup>3</sup> TWA  
250 ppm STEL; 325 mg/m<sup>3</sup> STEL  
Prevent or reduce skin absorption  
NIOSH: 200 ppm TWA; 260 mg/m<sup>3</sup> TWA  
250 ppm STEL; 325 mg/m<sup>3</sup> STEL  
Potential for dermal absorption

## B: Canadian Provincial Exposure Limits

### Toluene (108-88-3)

Alberta: 50 ppm TWA; 188 mg/m<sup>3</sup> TWA  
Substance may be readily absorbed through intact skin  
British Columbia: 50 ppm TWA  
Skin notation



# Material Safety Data Sheet

## Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

Manitoba: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL  
New Brunswick: 50 ppm TWA; 188 mg/m<sup>3</sup> TWA  
Skin - potential for cutaneous absorption  
NW Territories: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL  
Skin notation  
Nova Scotia: 50 ppm TWA  
Skin - potential significant contribution to overall exposure by the cutaneous route  
Nunavut: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL  
Skin notation  
Ontario: 50 ppm TWAEV  
Quebec: 150 ppm STEV; 565 mg/m<sup>3</sup> STEV  
100 ppm TWAEV; 377 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 188 mg/m<sup>3</sup> TWA; 50 ppm TWA  
235 mg/m<sup>3</sup> STEL; 60 ppm STEL  
Yukon: 100 ppm TWA; 375 mg/m<sup>3</sup> TWA  
150 ppm STEL; 560 mg/m<sup>3</sup> STEL  
Skin notation

### Methyl Acetate (79-20-9)

Alberta: 200 ppm TWA; 606 mg/m<sup>3</sup> TWA  
250 ppm STEL; 757 mg/m<sup>3</sup> STEL  
British Columbia: 200 ppm TWA  
Columbia: 250 ppm STEL  
Manitoba: 200 ppm TWA; 610 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL  
New Brunswick: 200 ppm TWA; 606 mg/m<sup>3</sup> TWA  
250 ppm STEL; 757 mg/m<sup>3</sup> STEL  
NW Territories: 200 ppm TWA; 605 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL  
Nova Scotia: 200 ppm TWA  
250 ppm STEL  
Nunavut: 200 ppm TWA; 605 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL  
Ontario: 200 ppm TWAEV; 605 mg/m<sup>3</sup> TWAEV  
250 ppm STEV; 755 mg/m<sup>3</sup> STEV  
Quebec: 250 ppm STEV; 760 mg/m<sup>3</sup> STEV  
200 ppm TWAEV; 606 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 606 mg/m<sup>3</sup> TWA; 200 ppm TWA  
757 mg/m<sup>3</sup> STEL; 250 ppm STEL  
Yukon: 200 ppm TWA; 610 mg/m<sup>3</sup> TWA  
250 ppm STEL; 760 mg/m<sup>3</sup> STEL

### Light Aliphatic Solvent Naphtha (8032-32-4)

Alberta: 300 ppm TWA; 1398 mg/m<sup>3</sup> TWA  
British Columbia: 350 mg/m<sup>3</sup> TWA  
Columbia: 300 ppm TWA; 1350 mg/m<sup>3</sup> TWA  
Manitoba: 300 ppm TWA; 1350 mg/m<sup>3</sup> TWA  
New Brunswick: 300 ppm TWA; 1370 mg/m<sup>3</sup> TWA  
NW Territories: 300 ppm TWA; 1350 mg/m<sup>3</sup> TWA  
400 ppm STEL; 1800 mg/m<sup>3</sup> STEL  
Nova Scotia: 300 ppm TWA  
Nunavut: 300 ppm TWA; 1350 mg/m<sup>3</sup> TWA  
400 ppm STEL; 1800 mg/m<sup>3</sup> STEL  
Ontario: 1350 mg/m<sup>3</sup> TWAEV  
Quebec: 300 ppm TWAEV; 1370 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 1370 mg/m<sup>3</sup> TWA; 300 ppm TWA



# Material Safety Data Sheet

## Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

1712 mg/m<sup>3</sup> STEL; 375 ppm STEL

### Dibutyl Phthalate (84-74-2)

Alberta: 5 mg/m<sup>3</sup> TWA  
British Columbia: 5 mg/m<sup>3</sup> TWA  
Columbia: 5 mg/m<sup>3</sup> TWA  
Manitoba: 5 mg/m<sup>3</sup> TWA  
New Brunswick: 5 mg/m<sup>3</sup> TWA  
NW Territories: 5 mg/m<sup>3</sup> TWA  
10 mg/m<sup>3</sup> STEL  
Nova Scotia: 5 mg/m<sup>3</sup> TWA  
Nunavut: 5 mg/m<sup>3</sup> TWA  
10 mg/m<sup>3</sup> STEL  
Ontario: 5 mg/m<sup>3</sup> TWAEV  
Quebec: 5 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 5 mg/m<sup>3</sup> TWA  
10 mg/m<sup>3</sup> STEL  
Yukon: 5 mg/m<sup>3</sup> TWA  
10 mg/m<sup>3</sup> STEL

### Heptane (n-) (142-82-5)

Alberta: 400 ppm TWA; 1640 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2050 mg/m<sup>3</sup> STEL  
British Columbia: 400 ppm TWA  
Columbia: 500 ppm STEL  
Manitoba: 400 ppm TWA; 1600 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2000 mg/m<sup>3</sup> STEL  
New Brunswick: 400 ppm TWA; 1640 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2050 mg/m<sup>3</sup> STEL  
NW Territories: 400 ppm TWA; 1640 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2049 mg/m<sup>3</sup> STEL  
Nova Scotia: 400 ppm TWA  
500 ppm STEL  
Nunavut: 400 ppm TWA; 1640 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2049 mg/m<sup>3</sup> STEL  
Ontario: 400 ppm TWAEV; 1635 mg/m<sup>3</sup> TWAEV  
500 ppm STEV; 2045 mg/m<sup>3</sup> STEV  
Quebec: 500 ppm STEV; 2050 mg/m<sup>3</sup> STEV  
400 ppm TWAEV; 1640 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 1640 mg/m<sup>3</sup> TWA; 400 ppm TWA  
2050 mg/m<sup>3</sup> STEL; 500 ppm STEL  
Yukon: 400 ppm TWA; 1600 mg/m<sup>3</sup> TWA  
500 ppm STEL; 2000 mg/m<sup>3</sup> STEL

### Carbon black (1333-86-4)

Alberta: 3.5 mg/m<sup>3</sup> TWA  
British Columbia: 3.5 mg/m<sup>3</sup> TWA  
Columbia: 3.5 mg/m<sup>3</sup> TWA  
Manitoba: 3.5 mg/m<sup>3</sup> TWA  
New Brunswick: 3.5 mg/m<sup>3</sup> TWA  
NW Territories: 3.5 mg/m<sup>3</sup> TWA  
7 mg/m<sup>3</sup> STEL  
Nova Scotia: 3.5 mg/m<sup>3</sup> TWA  
Nunavut: 3.5 mg/m<sup>3</sup> TWA  
7 mg/m<sup>3</sup> STEL  
Ontario: 3.5 mg/m<sup>3</sup> TWAEV  
Quebec: 3.5 mg/m<sup>3</sup> TWAEV  
Saskatchewan: 3.5 mg/m<sup>3</sup> TWA  
7 mg/m<sup>3</sup> STEL



# Material Safety Data Sheet

## Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

Yukon: 3.5 mg/m<sup>3</sup> TWA  
7 mg/m<sup>3</sup> STEL

### Methanol (67-56-1)

Alberta: 200 ppm TWA; 262 mg/m<sup>3</sup> TWA  
250 ppm STEL; 328 mg/m<sup>3</sup> STEL  
Substance may be readily absorbed through intact skin

British Columbia: 200 ppm TWA  
250 ppm STEL  
Skin notation

Manitoba: 200 ppm TWA; 260 mg/m<sup>3</sup> TWA  
250 ppm STEL; 310 mg/m<sup>3</sup> STEL  
skin - potential for cutaneous absorption

New Brunswick: 200 ppm TWA; 262 mg/m<sup>3</sup> TWA  
250 ppm STEL; 328 mg/m<sup>3</sup> STEL  
Skin - potential for cutaneous absorption

NW Territories: 200 ppm TWA; 262 mg/m<sup>3</sup> TWA  
250 ppm STEL; 328 mg/m<sup>3</sup> STEL  
Skin notation

Nova Scotia: 200 ppm TWA  
250 ppm STEL  
Skin - potential significant contribution to overall exposure by the cutaneous route

Nunavut: 200 ppm TWA; 262 mg/m<sup>3</sup> TWA  
250 ppm STEL; 328 mg/m<sup>3</sup> STEL  
Skin notation

Ontario: 200 ppm TWAEV; 260 mg/m<sup>3</sup> TWAEV  
250 ppm STEV; 325 mg/m<sup>3</sup> STEV  
Absorption through skin, eyes, or mucous membranes

Quebec: 250 ppm STEV; 328 mg/m<sup>3</sup> STEV  
200 ppm TWAEV; 262 mg/m<sup>3</sup> TWAEV  
Skin designation

Saskatchewan: 262 mg/m<sup>3</sup> TWA; 200 ppm TWA  
328 mg/m<sup>3</sup> STEL; 250 ppm STEL

Yukon: 200 ppm TWA; 260 mg/m<sup>3</sup> TWA  
250 ppm STEL; 310 mg/m<sup>3</sup> STEL  
Skin notation

### Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

#### Personal Protective Equipment: Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

#### Personal Protective Equipment: Skin

Use appropriate hand protection.

#### Personal Protective Equipment: Respiratory

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

#### Personal Protective Equipment: General

Use good industrial hygiene practices in handling this material.



# Material Safety Data Sheet

Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance:</b> Black	<b>Odor:</b> Solvent
<b>Physical State:</b> Liquid	<b>Flash Point:</b> Not Determined
<b>Flash Point Method:</b> N/A	<b>Boiling Point:</b> Not Determined
<b>Melting Point:</b> Not Determined	<b>Pour Point:</b> Not Determined
<b>Specific Gravity:</b> 1.0173	<b>Solubility (H2O):</b> Insoluble
<b>Vapor Pressure:</b> 55-75 PSIG	<b>Vapor Density:</b> Heavier Than Air
<b>Auto Ignition:</b> Not Determined	<b>Lower Flammability Limit:</b> Not Determined
<b>Upper Flammability Limit:</b> Not Determined	<b>pH:</b> Not Determined

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Chemical Stability

Stable under normal conditions.

### Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

### Incompatibility

This product may react with oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

### Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

### Possibility of Hazardous Reactions

Will not occur.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Acute Dose Effects

#### A: General Product Information

An LD50 value for this product has not been determined.

#### B: Component Analysis - LD50/LC50

##### Toluene (108-88-3)

Inhalation LC50 Rat: 12.5 mg/L/4H; Inhalation LC50 Rat: >26700 ppm/1H; Oral LD50 Rat: 636 mg/kg; Dermal LD50 Rabbit: 8390 mg/kg

##### Methyl Acetate (79-20-9)

Inhalation LC50 Rat: 16000 ppm/4H; Oral LD50 Rat: 5000 mg/kg; Dermal LD50 Rat: >2000 mg/kg; Dermal LD50 Rabbit: >5000 mg/kg

##### Light Aliphatic Solvent Naphtha (8032-32-4)

Inhalation LC50 Rat: 3400 ppm/4H

##### Dibutyl Phthalate (84-74-2)

Inhalation LC50 Rat: >15.68 mg/L/4H; Oral LD50 Rat: 6300 mg/kg; Dermal LD50 Rabbit: >2000 mg/kg

##### Heptane (n-) (142-82-5)

Inhalation LC50 Rat: 103 g/m<sup>3</sup>/4H

##### Carbon Black (1333-86-4)

Oral LD50 Rat: >15400 mg/kg; Dermal LD50 Rabbit: >3 g/kg

##### Naphtha (Petroleum), Heavy Aromatic (64742-94-5)

Inhalation LC50 Rat: 590 mg/m<sup>3</sup>/4H; Oral LD50 Rat: 7050 mg/kg; Dermal LD50 Rabbit: 2 mL/kg

##### Methanol (67-56-1)

Inhalation LC50 Rat: 83.2 mg/L/4H; Inhalation LC50 Rat: 64000 ppm/4H; Oral LD50 Rat: 5628 mg/kg;



# Material Safety Data Sheet

**Spray Rubberized Undercoating (Aerosol)**

**MSDS ID: 451**

Dermal LD50 Rabbit: 15800 mg/kg

## Carcinogenicity

### A: General Product Information

No carcinogenicity data available for this product.

### B: Component Carcinogenicity

#### Toluene (108-88-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71 [1999], Monograph 47 [1989] (Group 3 (not classifiable))

#### Light Aliphatic Solvent Naphtha (8032-32-4)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans

#### Carbon Black (1333-86-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

NIOSH: potential occupational carcinogen

IARC: Monograph 93 posted, Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))

## \*\*\* Section 12 - Ecological Information \*\*\*

### Ecotoxicity

No information available for the product.

## \*\*\* Section 13 - Disposal Considerations \*\*\*

### Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

## \*\*\* Section 14 - Transportation Information \*\*\*

### US DOT Information

**Shipping Name:** Consumer Commodity, ORM-D

### IMDG Information

**Shipping Name:** Aerosol, Flammable

**UN #:** 1950 **Hazard Class:** 2.1 **Required Label(s):** Limited Quantity

### IATA Information

**Shipping Name:** Aerosol, Flammable

**UN #:** 1950 **Hazard Class:** 2.1 **Required Label(s):** Limited Quantity

## \*\*\* Section 15 - Regulatory Information \*\*\*

### US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.

### A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).



# Material Safety Data Sheet

## Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

### Toluene (108-88-3)

SARA 313: 1.0 % de minimis concentration  
CERCLA: 1000 lb final RQ; 454 kg final RQ

### Dibutyl phthalate (84-74-2)

SARA 313: 1.0 % de minimis concentration  
CERCLA: 10 lb final RQ; 4.54 kg final RQ

### Methanol (67-56-1)

SARA 313: 1.0 % de minimis concentration  
CERCLA: 5000 lb final RQ; 2270 kg final RQ

### B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Petroleum gases, liquified, sweetened	68476-86-8	Yes	DSL	EINECS
Toluene	108-88-3	Yes	DSL	EINECS
Methyl acetate	79-20-9	Yes	DSL	EINECS
Light aliphatic solvent naphtha	8032-32-4	Yes	DSL	EINECS
Dibutyl phthalate	84-74-2	Yes	DSL	EINECS
Petroleum resins	64742-16-1	Yes	DSL	EINECS
Heptane (n-)	142-82-5	Yes	DSL	EINECS
Carbon black	1333-86-4	Yes	DSL	EINECS
Naphtha (petroleum), heavy aromatic	64742-94-5	Yes	DSL	EINECS
Methanol	67-56-1	Yes	DSL	EINECS

### State Regulations

Other state regulations may apply. Check individual state requirements.

### Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes	Yes
Methyl acetate	79-20-9	Yes	Yes	Yes	Yes	Yes	Yes
Light aliphatic solvent naphtha	8032-32-4	No	No	Yes	Yes	Yes	No
Dibutyl phthalate	84-74-2	Yes	Yes	Yes	Yes	Yes	Yes
Heptane (n-)	142-82-5	Yes	Yes	Yes	Yes	Yes	Yes
Carbon black	1333-86-4	Yes	Yes	Yes	Yes	Yes	Yes
Methanol	67-56-1	Yes	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

### Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Toluene	108-88-3	1 %
Methyl acetate	79-20-9	1 %
Light aliphatic solvent naphtha	8032-32-4	1 %
Dibutyl phthalate	84-74-2	1 %
Heptane (n-)	142-82-5	1 %
Carbon black	1333-86-4	1 %
Methanol	67-56-1	1 %



## Material Safety Data Sheet

Spray Rubberized Undercoating (Aerosol)

MSDS ID: 451

\* \* \* Section 16 - Other Information \* \* \*

### Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

### Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

**End of MSDS 451**