

Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner



1. Product and company identification

- Material uses** : Other non-specified industry: Cleaner.
- Manufacturer** : BG Products Inc.
701 S. Wichita Street
Wichita, KS, 67213, USA
www.bgprod.com
- MSDS #** : 464
- Validation date** : 4/26/2010.
- Responsible name** : Kolin Anglin, Environmental Coordinator
316-265-2686
msds@bgprod.com
- In case of emergency** : (800) 424-9300 (CHEMTREC)

2. Hazards identification

- Physical state** : Liquid.
- Odor** : Wintergreen.
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Emergency overview** : **EXTREMELY FLAMMABLE. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.**
Flammable aerosol. Avoid contact with skin and clothing. Contains material that may cause target organ damage, based on animal data.

Potential acute health effects

No known significant effects or critical hazards.

Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data.
- Target organs** : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes, central nervous system (CNS).

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Eyes** : Adverse symptoms may include the following:
irritation
redness

Medical conditions aggravated by over-exposure

- : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

Name	CAS number	%
Isobutane	75-28-5	1 - 5
Propanol, 1(or 2)-(2-methoxymethylethoxy)-	34590-94-8	1 - 5
Sodium hydroxide (Na(OH))	1310-73-2	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

- Flammability of the product** : Extremely flammable. Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**

6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits
Isobutane	<p>NIOSH REL (United States, 6/2008). TWA: 800 ppm 10 hour(s). TWA: 1900 mg/m³ 10 hour(s).</p>
Propanol, 1(or 2)-(2-methoxymethylethoxy)-	<p>ACGIH TLV (United States, 1/2008). TWA: 1000 ppm 8 hour(s).</p> <p>ACGIH TLV (United States, 1/2008). Absorbed through skin. TWA: 100 ppm 8 hour(s). TWA: 606 mg/m³ 8 hour(s). STEL: 150 ppm 15 minute(s). STEL: 909 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2008). Absorbed through skin. TWA: 100 ppm 10 hour(s). TWA: 600 mg/m³ 10 hour(s). STEL: 150 ppm 15 minute(s). STEL: 900 mg/m³ 15 minute(s).</p> <p>OSHA PEL (United States, 11/2006). Absorbed through skin. TWA: 100 ppm 8 hour(s). TWA: 600 mg/m³ 8 hour(s).</p>
Sodium hydroxide (Na(OH))	<p>ACGIH TLV (United States, 1/2008). C: 2 mg/m³</p> <p>NIOSH REL (United States, 6/2008). CEIL: 2 mg/m³</p> <p>OSHA PEL (United States, 11/2006).</p>

8. Exposure controls/personal protection

TWA: 2 mg/m³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: <-20°C (<-4°F)
Auto-ignition temperature	: Not available.
Flammable limits	: Not available.
Color	: Colorless.
Odor	: Wintergreen.
pH	: 11.7
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Specific gravity	: 1.027
Vapor pressure	: Not available.
Vapor density	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
Solubility	: Easily soluble in the following materials: cold water and hot water.

9. Physical and chemical properties

Density : 8.565 (lbs/gal)

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Materials to avoid : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isobutane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours

12. Ecological information

Product/ingredient name	Result	Species	Exposure
Sodium hydroxide (Na(OH))	Acute EC50 40.38 mg/L Fresh water	Daphnia - Ceriodaphnia dubia - Neonate - <24 hours	48 hours
	Acute LC50 33000 to 100000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 125000 ug/L Fresh water	Fish - Gambusia affinis - Adult	96 hours
	Chronic NOEC 56 mg/L Marine water	Fish - Poecilia reticulata - Young - 3 to 4 weeks	96 hours

Octanol/water partition coefficient : Not available.

13. Disposal considerations



Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Do not puncture or incinerate container.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification		Consumer commodity	ORM-D			-
IMDG Class	UN1950	AEROSOLS, flammable	2.1	-		Emergency schedules (EmS) F-D, S-U Remarks Limited quantity
IATA-DGR Class	UN1950	AEROSOLS, flammable	2.1	-		Remarks Limited quantity

PG* : Packing group

15. Regulatory information

United States

HCS Classification

: Flammable liquid
Target organ effects

U.S. Federal regulations

: **TSCA 4(a) final test rules:** Propanol, 1(or 2)-(2-methoxymethylethoxy)-
TSCA 8(a) PAIR: Propanol, 1(or 2)-(2-methoxymethylethoxy)-; Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-
United States inventory (TSCA 8b): All components are listed or exempted.
TSCA 12(b) one-time export: Propanol, 1(or 2)-(2-methoxymethylethoxy)-
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Isobutane ; Propanol, 1(or 2)-(2-methoxymethylethoxy)-; Sodium hydroxide (Na(OH))
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
Isobutane : Fire hazard, Sudden release of pressure; Propanol, 1(or 2)-(2-methoxymethylethoxy)-: Fire hazard, Immediate (acute) health hazard; Sodium hydroxide (Na(OH)): Immediate (acute) health hazard
Clean Water Act (CWA) 311: Sodium hydroxide (Na(OH))
Clean Air Act (CAA) 112 accidental release prevention: Isobutane
Clean Air Act (CAA) 112 regulated flammable substances: Isobutane

State regulations

Massachusetts

: The following components are listed: ISOBUTANE; DIPROPYLENE GLYCOL METHYL ETHER; SODIUM HYDROXIDE

New York

: The following components are listed: Sodium hydroxide

New Jersey

: The following components are listed: Isobutane; DIPROPYLENE GLYCOL METHYL ETHER; SODIUM HYDROXIDE

Pennsylvania

: The following components are listed: PROPANE, 2-METHYL-; PROPANOL, (2-METHOXYMETHYLETHOXY)-; SODIUM HYDROXIDE (NA(OH))

Rhode Island

: None of the components are listed.

United States inventory (TSCA 8b)

: All components are listed or exempted.

Canada

WHMIS (Canada)

: Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).
Class E: Corrosive material

15. Regulatory information

Canadian lists

- Canadian NPRI** : The following components are listed: Butane; Nonylphenol and its ethoxylates
CEPA Toxic substances : The following components are listed: Nonylphenol and its ethoxylates
Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

- International lists** : **Australia inventory (AICS)**: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: All components are listed or exempted.
Korea inventory: All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.

16. Other information

Hazardous Material Information System (U.S.A.) :

Health	*	0
Flammability		4
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

- Date of issue** : 4/26/2010.
Date of previous issue : No previous validation.
Version : 1

☑ Indicates information that has changed from previously issued version.

Notice to reader

16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.