



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

*** Section 1 - Chemical Product and Company Identification ***

Part Number: 464

Product Use: BG Vinyl & Leather Cleaner & Conditioner

Manufacturer Information

BG Products Inc.
701 S. Wichita Street
Wichita, KS 67213

Phone: (316) 265-2686
Fax: (316) 265-0718
Emergency # 1-800-424-9300 (CHEMTREC)

*** Section 2 - Hazards Identification ***

Emergency Overview

DANGER

- CONTENTS UNDER PRESSURE.
- EXTREMELY FLAMMABLE. Vapors may cause flash fire or explosion.
- EYE AND SKIN IRRITANT. Avoid contact with eyes, skin, and clothing.
- This product may be harmful by inhalation. Avoid prolonged breathing of fumes. Use with adequate ventilation.
- This product may be harmful if it is swallowed.

HMIS Ratings: Health: 3 Fire: 1 Physical Hazard: 0 Pers. Prot.: B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
7732-18-5	Water	60-100
75-28-5	Isobutane	5
34590-94-8	Dipropylene glycol monomethyl ether	4
9016-45-9	Ethylene oxide-Nonylphenol polymer	1-3
1310-73-2	SODIUM HYDROXIDE	1-3

Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention.

First Aid: Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.

First Aid: Inhalation



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.
Keep away from heat, sparks, or open flame.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing.
Fire fighters should avoid inhaling any combustion products.

NFPA Ratings: Health: 3 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Contain the discharged material. Remove sources of ignition.

Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material.
Shovel material into appropriate container for disposal.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

Special Procedures

Wear appropriate personal protective equipment.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Isobutane (75-28-5)

ACGIH: 1000 ppm TWA (listed under Aliphatic hydrocarbon gases alkane C1-C4)

NIOSH: 800 ppm TWA; 1900 mg/m³ TWA



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

Dipropylene glycol monomethyl ether (34590-94-8)

ACGIH: 100 ppm TWA
150 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route

OSHA: 100 ppm TWA; 600 mg/m³ TWA
150 ppm STEL; 900 mg/m³ STEL
Prevent or reduce skin absorption

NIOSH: 100 ppm TWA; 600 mg/m³ TWA
150 ppm STEL; 900 mg/m³ STEL
Potential for dermal absorption

SODIUM HYDROXIDE (1310-73-2)

ACGIH: 2 mg/m³ Ceiling
OSHA: 2 mg/m³ Ceiling
NIOSH: 2 mg/m³ Ceiling

B: Canadian Provincial Exposure Limits

Isobutane (75-28-5)

Manitoba: 1000 ppm TWA (listed under Aliphatic hydrocarbon gases alkane C1-C4)
Nova Scotia: 1000 ppm TWA (listed under Aliphatic hydrocarbon gases alkane C1-C4)

Dipropylene glycol monomethyl ether (34590-94-8)

Alberta: 100 ppm TWA; 606 mg/m³ TWA
150 ppm STEL; 909 mg/m³ STEL
Substance may be readily absorbed through intact skin

British Columbia: 100 ppm TWA
150 ppm STEL
Skin notation

Manitoba: 100 ppm TWA
150 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route

New Brunswick: 100 ppm TWA; 606 mg/m³ TWA
150 ppm STEL; 909 mg/m³ STEL
Skin - potential for cutaneous absorption

NW Territories: 100 ppm TWA; 606 mg/m³ TWA
150 ppm STEL; 909 mg/m³ STEL

Nova Scotia: 100 ppm TWA
150 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route

Nunavut: 100 ppm TWA; 606 mg/m³ TWA
150 ppm STEL; 909 mg/m³ STEL

Ontario: 100 ppm TWAEV; 605 mg/m³ TWAEV
150 ppm STEV; 910 mg/m³ STEV

Quebec: 150 ppm STEV; 909 mg/m³ STEV
100 ppm TWAEV; 606 mg/m³ TWAEV
Skin designation

Saskatchewan: 606 mg/m³ TWA; 100 ppm TWA
909 mg/m³ STEL; 150 ppm STEL

SODIUM HYDROXIDE (1310-73-2)

British Columbia: 2 mg/m³ Ceiling

Manitoba: 2 mg/m³ Ceiling

New Brunswick: 2 mg/m³ Ceiling

NW Territories: 2 mg/m³ Ceiling

Nova Scotia: 2 mg/m³ Ceiling

Nunavut: 2 mg/m³ Ceiling



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

Ontario: 2 mg/m3 CEV
 Quebec: 2 mg/m3 Ceiling
 Saskatchewan: 2 mg/m3 Ceiling
 Yukon: 2 mg/m3 Ceiling

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

Personal Protective Equipment: Skin

Use appropriate hand protection.

Personal Protective Equipment: Respiratory

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

Personal Protective Equipment: General

Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Appearance: Colorless	Odor: Pine Odor
Physical State: Compressed Gas	Flash Point: Not Determined
Flash Point Method:	Boiling Point: Not Determined
Melting Point: Not Determined	Pour Point: Not Determined
Specific Gravity: 1.027	Bulk Density: 8.570 lbs/gal
Solubility (H2O): Complete	Vapor Pressure: 45 psig
Vapor Density: 2	Auto Ignition: Not Available
Lower Flammability Limit: Not Available	Upper Flammability Limit: Not Available
pH: 11.7	

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

Incompatibility

This product may react with oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

A: General Product Information

An LD50 value for this product has not been determined.

B: Component Analysis - LD50/LC50

Water (7732-18-5)

Oral LD50 Rat: >90 mL/kg

Isobutane (75-28-5)

Inhalation LC50 Rat: 658 mg/L/4H

Dipropylene glycol monomethyl ether (34590-94-8)

Oral LD50 Rat: 5230 mg/kg; Dermal LD50 Rabbit: 9500 mg/kg

SODIUM HYDROXIDE (1310-73-2)

Dermal LD50 Rabbit: 1350 mg/kg

Ethylene oxide-Nonylphenol polymer (9016-45-9)

Oral LD50 Rat: 1310 mg/kg; Dermal LD50 Rabbit: 2 mL/kg

Carcinogenicity

A: General Product Information

No carcinogenicity data available for this product.

B: Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

*** Section 12 - Ecological Information ***

Ecotoxicity

No information available for the product.

*** Section 13 - Disposal Considerations ***

Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

*** Section 14 - Transportation Information ***

US DOT Information

Shipping Name: Consumer Commodity, ORM-D

IMDG Information

Shipping Name: Aerosols, Flammable

UN #: 1950 **Hazard Class:** 2.1

Required Label(s): Limited Quantity

IATA Information

Shipping Name: Aerosols, Flammable

UN #: 1950 **Hazard Class:** 2.1

Required Label(s): Limited Quantity

*** Section 15 - Regulatory Information ***

US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.



Material Safety Data Sheet

BG Vinyl & Leather Cleaner & Conditioner

MSDS ID: 464

A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

SODIUM HYDROXIDE (1310-73-2)

CERCLA: 1000 lb final RQ; 454 kg final RQ

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Water	7732-18-5	Yes	DSL	EINECS
Isobutane	75-28-5	Yes	DSL	EINECS
Dipropylene glycol monomethyl ether	34590-94-8	Yes	DSL	EINECS
SODIUM HYDROXIDE	1310-73-2	Yes	DSL	EINECS
Ethylene oxide-Nonylphenol polymer	9016-45-9	Yes	DSL	No

State Regulations

Other state regulations may apply. Check individual state requirements.

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Isobutane	75-28-5	No	Yes	No	Yes	Yes	No
Dipropylene glycol monomethyl ether	34590-94-8	Yes	Yes	Yes	Yes	Yes	Yes
SODIUM HYDROXIDE	1310-73-2	Yes	Yes	Yes	Yes	Yes	Yes

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Dipropylene glycol monomethyl ether	34590-94-8	1 %
SODIUM HYDROXIDE	1310-73-2	1 %

*** Section 16 - Other Information ***

Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

Contact: Kolin Anglin, Environmental Coordinator

Contact Phone: 316-265-2686

End of MSDS 464